

275 MULCHER

BRON
POWER TO PERFORM



The BRON 275 Mulcher is the right machine to tackle jobs such as right of way clearing for seismic lines, electric and power lines, pipelines, clearing for commercial sites, recreational trails, golf courses, building lots, and forestry fireguards!

HYDRAULIC TILTING CAB
HEAVY DUTY FINAL DRIVES
HIGH EFFICIENCY COOLING PACKAGE
D3 WITH OPTIONAL D4 UNDERCARRIAGE

3.5 PSI *WITH HEAD

LOW GROUND PRESSURE

OSCILLATING
TRACK FRAMES

MANOEUVRABILITY

275 HP CAT C7 ENGINE


EFFICIENT POWER

FEATURES




ERGONOMIC DESIGN

Pressurized cab has joystick steering & seating designed for operator comfort with height, headrest & seat tilt adjustments & air-ride suspension to eliminate operator fatigue.



OSCILLATING TRACK FRAME

Frames pivot freely with heavy-duty chain guides for constant surface contact & maximum traction. Wide tracks add stability & floatation in sensitive environments.



REMOVABLE BELLY PANS

For easy cleanout & service with recessed fasteners for a smooth underside.



TILTING CAB, LEXAN & ROPS/FOPS/OPS

1 1/4" Lexan™ windshield protects the operator from high speed debris. ROPS, FOPS, & OPS certified for added safety. Tilting cab for easy access.



SERVICE LIGHTS

An LED light is located within the engine bay with an additional LED light underneath the cab for better visibility during service & maintenance.



COLD START & LOW RUNNING TEMP

Intake manifold grid pre-heat warms the engine while oversized heat exchangers & a proportional fan circuit cool as needed.

OPTIONS



LED LIGHTS

1200 Lumen, 6 on the front & 2 on the back or high output of 2500 Lumen also available.



FIRE SUPPRESSION

Minimize damage & increase safety in the unexpected event of a fire.



HYDRAULIC WINCH

DP Winch or Warn Winch are available.



REAR-VIEW CAMERA

The rear-view camera reduces the need to look over your shoulder, allowing you to focus on the task at hand!



FRONT WINDOW GUARD

The front window guard protects the front window from large branches.



CAB AIR CHUCK

Compressed air lines to make maintenance & clean up easier.

MULCHER SPECIFICATIONS

Operating Weight with Head - lbs (kg)	27,500 (12,473)
Overall Width - in. (mm)	94" (2387)
Overall Height - in. (mm)	122" (3099)
Overall Length - in. (mm)	180" (4572)
Cab	Tilting cab with climate control (ROPS, FOPS & OPS)
Steering	Joystick control
Engine Make & Model	Caterpillar® C7 Acert
Emissions Certified	Tier III
Rating	2200 rpm
Power - hp (KW)	275 (205)
Torque - ft.lbs.	927
Fuel Tank Capacity - U.S. Gal. (L)	100 (360)
Ground Pressure with Head - psi (kPa)	3.5 (24.1)
Ground Clearance - in. (mm)	19" (483)
Undercarriage	D3 (D4 optional)
Suspension	Oscillating track frames
Travel Speed - mph (kph)	3.6 (5.7)



www.rwfbbron.com

Toll Free: 1-800-263-1060
Tel: 1-519-421-0036 | Fax: 519-421-0028
Email: info@rwfbbron.com

873 Devonshire Avenue,
Woodstock, Ontario, Canada, N4S 8Z4